

## - Aluminum Alloy Wheels

- Roof Light/Electric Winch
- 5 Speed Manuel Clutch
- Side Entry Door
- 4 Wheel Independent Suspension

## 4Wheel Drive



Engine Model /Displacement	4 Cylinder, 4 Stroke, 970cc
<ul> <li>Cooling System</li> </ul>	Liquid Cool
<ul> <li>Bore</li> </ul>	62.0
<ul> <li>Stroke</li> </ul>	66.0
<ul> <li>Compression Ratio</li> </ul>	8.7
<ul> <li>Max power</li> </ul>	34.68 HP / 5500 RPM
<ul> <li>Max Torque</li> </ul>	55 Lb-Ft / 3000 RPM
<ul> <li>Max Horse Power(HP)</li> </ul>	34.68 HP / 5500 RPM
<ul> <li>Starter System</li> </ul>	Electric Ignition
<ul> <li>Ignition Type</li> </ul>	C.D.I
<ul> <li>Lubrication</li> </ul>	Wet Sump
Engine Oil	SAE15W/40SG
<ul> <li>Transmission / Drive Line</li> </ul>	5 Speed Electric Shift / Shaft Drive
<ul> <li>Overall L X W X H (in)</li> </ul>	146 X 63 X 74
<ul> <li>Wheel Base</li> </ul>	106
<ul> <li>Ground Clearance</li> </ul>	12.00
<ul> <li>Seat Height</li> </ul>	33.00
<ul> <li>Rider Capacity</li> </ul>	4
Dry Weight	1146
<ul> <li>Gross Weight</li> </ul>	1488
Brake (F / R)	Disc/Disc
Tire Front	25 x 8-12
<ul> <li>Tire Rear</li> </ul>	25 x 10-12
<ul> <li>Fuel Tank Capacity</li> </ul>	8.0
<ul> <li>Suspension Front</li> </ul>	4 Wheel Independent Suspension
<ul> <li>Suspension Rear</li> </ul>	4 Wheel Independent Suspension
<ul> <li>AGE Restriction</li> </ul>	16
<ul> <li>Load Capacity</li> </ul>	441
<ul> <li>Battery</li> </ul>	12V / 48 Ah
<ul> <li>Climbing Ability</li> </ul>	30
Package L X W X H (in)	146.00 X 63.00 X 50.00
<ul> <li>Qty for 40HQ</li> </ul>	6











\_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_

- 4 Wheel Independent Suspension
- Front / Rear Differential
- High & Low (Selectable 4x4 or 4x2)
- Aiuminum Wheels



## Electric Shifter / Electric Winch / Digital Display - Engine Model / Displacement Single Cylinder, 4 stroke, 359 cc - Cooling System Liquid cool



Electric Shifter



4 Wheel Independent Suspension



Digital Display



Inner Differential



400cc HONDA Style Engine

<ul> <li>Cooling System</li> </ul>	Liquid cool	
<ul> <li>Bore</li> </ul>	75.8	
<ul> <li>Stroke</li> </ul>	74.2	
<ul> <li>Compression Ratio</li> </ul>	8.8	
<ul> <li>Max power</li> </ul>	18.36 HP / 5200 RPM	
<ul> <li>Max Torque</li> </ul>	18 Lb-Ft / 4000 RPM	
<ul> <li>Max Horse Power(HP)</li> </ul>	18.36 HP	
<ul> <li>Starter System</li> </ul>	Electric Start/Pull Start	
<ul> <li>Ignition Type</li> </ul>	C.D.I	
<ul> <li>Lubrication</li> </ul>	10W-30	
<ul> <li>Engine Oil</li> </ul>	SAE15W/40SG	
<ul> <li>Transmission / Drive Line</li> </ul>	5 Speed Electric Shift/Shaft Drive	
<ul> <li>Overall L X W X H (in)</li> </ul>	83 <b>X</b> 47 <b>X</b> 47	
<ul> <li>Wheel Base</li> </ul>	52	
<ul> <li>Ground Clearance</li> </ul>	12	
<ul> <li>Seat Height</li> </ul>	36	
<ul> <li>Rider Capacity</li> </ul>	1	
Dry Weight	686	
<ul> <li>Gross Weight</li> </ul>	785	
Brake (F / R)	Disc/Disc	
<ul> <li>Tire Front</li> </ul>	25 x 8-12	
<ul> <li>Tire Rear</li> </ul>	25 x 10-12	
<ul> <li>Fuel Tank Capacity</li> </ul>	3.5	
<ul> <li>Suspension Front</li> </ul>	4 wheel Independent Suspension	
<ul> <li>Suspension Rear</li> </ul>	4 wheel Independent Suspension	
<ul> <li>AGE Restriction</li> </ul>	16	
<ul> <li>Load Capacity</li> </ul>	Front : 66 lbs. / Rear : 132 lbs.	
<ul> <li>Battery</li> </ul>	12V / 14 Ah	
<ul> <li>Climbing Ability</li> </ul>	30	
Package L X W X H (in)	87 <b>X</b> 45 <b>X</b> 33	
<ul> <li>Qty for 40HQ</li> </ul>	30	








- 4 Wheel Independent Suspension
- Front / Rear Differential
- High & Low (Selectable 4x4 or 4x2)
- Aiuminum Wheels

4x4Shaft Drive

## Electric Shifter / Electric Winch / Digital Display





**E.P.A**. C.A.R.B

20. ···





- Aiuminum Alloy Wheels
- Rear Differential Independent Suspension

ATV SODGE UTILITY

\_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_

- Fully Automatic / Foot Brake
- Digital Indicator
- 4x2

Rear Differential





Engine Model /Displacem	ent Single Cylinder, 4-Stroke / 276c
Cooling System	Water Cooled
Bore	72.
Stroke	66.8
Compression Ratio	10.3
Max power	21.5 HP / 6500 RPM
Max Torque	17 Lb-Ft / 5500 RPM
Max Horse Power(HP)	21.5 HI
Starter System	Electronic Ignition
Ignition Type	C.D.
Lubrication	Wet Sump
Engine Oil	SAE15W/40S0
Transmission / Drive Line	Fully Automatic with Reverse / Shaft Drive
Overall L X W X H (in)	67.00 X 44.00 X 34.00
Wheel Base	50.00
Ground Clearance	10.00
Seat Height	32.50
Rider Capacity	
Dry Weight	418
Gross Weight	530
Brake (F/R)	Disc / Disc
Tire Front	25x8-12
Tire Rear	25x10-12
Fuel Tank Capacity	4.0
Suspension Front	Independent Strut
Suspension Rear	Independent Suspension, Coil over shocks
AGE Restriction	10
Load Capacity	344
Battery	12V / 14A
Climbing Ability	25 X 67.00 X 44.00
Package L X W X H (in)	34.00
Qty for 40HQ	2

A model

















Engine Model /Displacem	ent Single Cylinder, 4-Stroke / 276cc
<ul> <li>Cooling System</li> </ul>	Water Cooled
<ul> <li>Bore</li> </ul>	72.5
<ul> <li>Stroke</li> </ul>	66.8
<ul> <li>Compression Ratio</li> </ul>	10.3
<ul> <li>Max power</li> </ul>	21.5 HP / 6500 RPM
<ul> <li>Max Torque</li> </ul>	17 Lb-Ft / 5500 RPM
<ul> <li>Max Horse Power(HP)</li> </ul>	21.5 HP
<ul> <li>Starter System</li> </ul>	Electronic Ignition
<ul> <li>Ignition Type</li> </ul>	C.D.I.
<ul> <li>Lubrication</li> </ul>	Wet Sump
<ul> <li>Engine Oil</li> </ul>	SAE15W/40SG
<ul> <li>Transmission / Drive Line</li> </ul>	Fully Automatic with Reverse / Shaft Driven
<ul> <li>Overall L X W X H (in)</li> </ul>	91.16 X 51.57 X 32.68
<ul> <li>Wheel Base</li> </ul>	50.43
<ul> <li>Ground Clearance</li> </ul>	7.21
<ul> <li>Seat Height</li> </ul>	32.50
<ul> <li>Rider Capacity</li> </ul>	1
<ul> <li>Dry Weight</li> </ul>	613
<ul> <li>Gross Weight</li> </ul>	754
Brake (F/R)	Disc / Disc
<ul> <li>Tire Front</li> </ul>	25x8-12
<ul> <li>Tire Rear</li> </ul>	25x10-12
<ul> <li>Fuel Tank Capacity</li> </ul>	4.0
Suspension Front	Independent Struts
<ul> <li>Suspension Rear</li> </ul>	Solid axle, Coil over shock
<ul> <li>AGE Restriction</li> </ul>	16
<ul> <li>Load Capacity</li> </ul>	344
<ul> <li>Battery</li> </ul>	12V / 14Ah
<ul> <li>Climbing Ability</li> </ul>	25
Package L X W X H (in)	90.16 X 51.57 X 32.68
<ul> <li>Qty for 40HQ</li> </ul>	27



- Heel Shifter
- New Swing Arm System
- Middle Size Utility Style (Not Mini Size)



Rear Reservoir Brake





Polished Muffler

Strong

Foot Deck

J	Iron	Rim	
---	------	-----	--

	110CC	150CC
	Single Cylinder, 4 Stroke, SOHC / 107cc	
<ul> <li>Cooling System</li> </ul>	Air Cooled	Air Cooled
<ul> <li>Bore</li> </ul>	52.4	57.0
<ul> <li>Stroke</li> </ul>	49.5	57.8
<ul> <li>Compression Ratio</li> </ul>	9.1	9.0
<ul> <li>Max power</li> </ul>	7.5 HP / 8000 RPM	8.86 HP / 7500 RPM
<ul> <li>Max Torque</li> </ul>	4.8 Lb-Ft / 7000 RPM	7 Lb-Ft / 5500 RPM
Max Horse Power(HP)	7.5 HP	8.86 HP
Starter System	Electric Starter	Electronic Ignition
Ignition Type	C.D.I.	C.D.I
Lubrication	Wet Sump	Wet Sump
Engine Oil	SAE 5W/30-15W/40	SAE10W-30
Transmission / Drive Line	3 Speed with Reverse / Chain Drive	Automatic / Chain Drive
Overall L X W X H (in)	65.00 X 36.64 X 29.15	63.40 X 35.50 X 40.50
Wheel Base	40.30	43.70
Ground Clearance	11.00	12.00
Seat Height	26.00	29.00
Rider Capacity	1	1
Dry Weight	368	315
Gross Weight	440	370
Brake(F/R)	Drum / Disc	Drum / Disc
Tire Front	19×7-8	19x7-8/2.9
Tire Rear	18x8-8	19x9.5-8
Fuel Tank Capacity	2.0	2.0
Suspension Front	Dual A Arm with coil over shocks	Dual A-Arm with coil over shocks
<ul> <li>Suspension Rear</li> </ul>	Swing Arm, Single coil over	Swing Arm with single coil over shock
<ul> <li>AGE Restriction</li> </ul>	16	18
Load Capacity	209	200
Battery	12V / 7Ah	12V/9Ah
Climbing Ability	Х	15
Package L X W X H (in)	63.40 X 35.40 X 28.30	58.00 X 33.00 X 31.00
Qty for 40HQ	42	63







- Mini Size of 110cc ATV
- New Design
- Front:Drum / Rear:Disc Brake
- Fully Automatic



E.P.A

Single Cylinder, 4 Stroke, ,110cc

С

.A.R.B

Air Cooled







BLUE CAMO



GREEN САМО



















<ul> <li>Cooling system</li> </ul>	Air Cooled
<ul> <li>Bore</li> </ul>	2.1 inch
<ul> <li>Stroke</li> </ul>	1.9 inch
<ul> <li>Compression Ratio</li> </ul>	9.1
<ul> <li>Max power</li> </ul>	7.3 HP / 8000 RPM
<ul> <li>Max Torque</li> </ul>	6.5 NM / 5500
<ul> <li>Max Horse Power(HP)</li> </ul>	7.3 HP
<ul> <li>Starter System</li> </ul>	Electric
<ul> <li>Ignition Type</li> </ul>	C.D.I
<ul> <li>Lubrication</li> </ul>	Wet Sump
<ul> <li>Engine Oil</li> </ul>	SAE 5W/30-15W/40
Transmission / Drive Line	3 Speed Fully Automatic / Chain Drive
Overall L X W X H (in)	57.1 X 36.6 X 36.2
<ul> <li>Wheel Base</li> </ul>	37.8
<ul> <li>Ground Clearance</li> </ul>	3.35
<ul> <li>Seat Height</li> </ul>	22
<ul> <li>Rider Capacity</li> </ul>	1
<ul> <li>Dry Weight</li> </ul>	198
<ul> <li>Gross Weight</li> </ul>	239
Brake(F/R)	Drum/Disc
<ul> <li>Tire Front</li> </ul>	16 x 8-7
<ul> <li>Tire Rear</li> </ul>	16 x 8-7
Fuel Tank Capacity	0.63
<ul> <li>Suspension Front</li> </ul>	Dual A arm w/ coil over shock
<ul> <li>Suspension Rear</li> </ul>	Swing arm, Single coil cover
<ul> <li>AGE Restriction</li> </ul>	12
<ul> <li>Load Capacity</li> </ul>	160
<ul> <li>Battery</li> </ul>	12V / 4 Ah
<ul> <li>Climbing Ability</li> </ul>	Х
Package L X W X H (in)	54.7 X 30.3 X 29.1
Qty for 40HQ	75

Engine Model /Displacement

in a Cu